Product Sheet ISGS[®] TECHNOLOGY

ISGS[®] TECHNOLOGY FOR NON-AQUEOUS PHASE LIQUIDS (NAPL)

Evonik's **ISGS**° **TECHNOLOGY** utilizes a permanganate-based solution to geochemically stabilize non-aqueous phase liquids (NAPL) in the aquifer. Permanganate and other proprietary reagents are selected depending upon the particular characteristics of each location and custom mixed on site into an aqueous solution that can be injected into an aquifer either through existing wells or direct push technology. As the solution migrates through the treatment area it oxidizes contaminants yielding partial mass removal. This in situ geochemical stabilization (ISGS) technology also reacts with contaminants in the treated area thereby coating NAPL surfaces with stable mineral precipitates that reduce mass flux.

THE SOUND SCIENCE OF ISGS®

In the presence of an organic compound (R), permanganate reacts to yield an oxidized intermediate, carbon dioxide, and manganese dioxide:

$R + MnO_4 \rightarrow MnO_2 + CO_2 \text{ or } ROx$

Proprietary additives are added to the solution to form mineral "crusts" or "shells" that are similar to birnessite $(Na_{0.3}Ca_{0.1}K_{0.1})(Mn^{4+},Mn^{3+})_2O_4 \cdot 1.5 H_2O$, which is an oxide mineral of manganese along with calcium, potassium and sodium.

Field Data from a field application of an ISGS[®] formulation at a site in Denver, CO are summarized on the following tables:

Contaminant (mg/kg)	Average (n=4) Background Treated		% Mass Reduction
LMH PAHs	7,633.50	5,996.75	21
HMW PAHs	1,961.55	1,744.55	10
TOTAL PAHs	9,595.05	7,771.30	19
PENTA	236.00	55.67	76
TOTAL CPs	284.48	59.25	79

 Table 1 Mass Reduction following a single ISGS® Treatment



Soil core from a site in Gainesville, Florida treated with ISGS®TECHNOLOGY.

Contaminant (mg/L)	Average (n=4) Background	Average (n=4) Treated	% Flux Reduction
LMH PAHs	34.41	12.75	73
HMW PAHs	6.05	0.11	99
TOTAL PAHs	40.46	12.86	79
PENTA	18.91	9.66	49
TOTAL CPs	23.38	10.41	56

Table 2 Mass Flux Reduction following a single ISGS® Treatment

KEY BENEFITS

When released into the environment, chlorinated solvents, coal tar, creosote and heavy crude oil are frequently present as DNAPL and represent a long-term secondary source of contamination. Physical removal or in situ remediation of DNAPL is not always practicable due to the depth of contamination, aquifer geology or the presence of physical surface structures. In these cases hydraulic containment (e.g., long-term pump-and-treat) or in situ stabilization is the only viable remedial action. ISGS® TECHNOLOGY can represent a more effective and cost-efficient alternative to conventional cement stabilization since the aqueous solution can be injected into an aquifer where it will follow preferred flow paths.

Representative ISGS® chemical costs:

Site Location	Geology	Delivery Method	Contaminants	Approx. Cost – \$USD/M³
Denver, CO	Dense Alluvium	Fixed Wells	PAHs, Pentachlorophenol	\$40 – 50
Dolomite, AL	Fractured Karst	Direct Push	Phase Separated Creosote	\$45 – 50
Gainesville, FL	Sand/Silt	Direct Push and Fixed Wells	Phase Separated Creosote	\$60 – 75

For more information and detailed case studies, please visit our website.

Disclaimer This information and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Recipients of this information and recommendations must make their own determination as to its suitability for their purposes. In no event shall Evonik assume liability for damages or losses of any kind or nature that result from the use of or reliance upon this information and recommendations. EVONIK EXPRESSLY DISCLAIMS ANY REPRESENTATIONS AND WARRANTIES OF ANY KIND, WHETHER EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS, NON-INFRINGEMENT, MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE (EVEN IF EVONIK IS AWARE OF SUCH PURPOSE) WITH RESPECT TO ANY INFORMATION AND RECOMMENDATIONS PROVIDED. Reference to any trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product, and does not imply that similar products could not be used. Evonik reserves the right to make any changes to the information and/or recommendations at any time, without prior or subsequent notice.

EVONIK INDUSTRIES AG

Active Oxygens remediation@evonik.com www.evonik.com/remediation

