

AN ALL-IN-ONE COMBINED REMEDY APPROACH TO ADDRESS SOIL AND GROUNDWATER CONTAMINATION

KLOZUR® CR, a Combined Remedy technology, is comprised of a specially formulated mixture of KLOZUR® SP and PERMEOX® ULTRA. KLOZUR® CR is a single, all-in-one formulated product that can be readily applied to either source areas or plumes with mixed petroleum and chlorinated solvents contamination. KLOZUR® CR destroys contaminants in soil and groundwater by promoting three modes of action: KLOZUR® activated persulfate chemical oxidation, aerobic bioremediation and anaerobic bioremediation.

KEY BENEFITS

Two field proven technologies formulated into an all-in-one preblended product.

- The Power of KLOZUR® Activated Persulfate
 - A built in KLOZUR® persulfate activator delivers proven and powerful chemical oxidation action from generated sulfate and hydroxyl radicals
 - Rapid in situ chemical oxidation to target source and hot spot contaminate zones, typically lasting 3-6 months
- The Performance of PERMEOX® ULTRA
 - Engineered calcium peroxide providing extended oxygen release for up to one year; longer than any other oxygen release compound available
 - Longevity delivers enhanced aerobic bioremediation in down gradient plumes



THE SOUND SCIENCE OF KLOZUR® CR

KLOZUR® CR provides self-activating KLOZUR® persulfation oxidation technology, utilizing the alkalinity generated by calcium peroxide to achieve a pH in the range of 11. In addition, the calcium peroxide will slowly generate hydrogen peroxide allowing for peroxide activation of persulfate. High pH activated persulfate is capable of destroying a wide range of contaminants, including petroleum hydrocarbons and chlorinated solvents.

Following the initial chemical oxidation phase, KLOZUR® CR will continue to release oxygen to be used as an electron receptor for aerobic bioremediation for up to a year, as a result of the slow hydration of the engineered calcium peroxide. Diffusion and transport of oxygen downgradient will support contaminant reductions in plume areas, treating BTEX, PAH's and petroleum hydrocarbons.

As a result of the persulfate oxidation with organic compounds, generated sulfate ions can be utilized by sulfate reducing bacteria as an electron acceptor under anaerobic conditions to degrade BTEX, PAH's and petroleum hydrocarbons.

APPLICATION METHODS

- Direct push injection
- Soil blending
- Direct application in an excavation

EXAMPLES OF CONTAMINANTS OF CONCERN

CHLORINATED SOLVENTS

PCE, TCE, DCE, VC, TCA, DCA

PETROLEUM

GRO, DRO, ORO, BTEX

PAHs

Creosote, MGP residuals 1,4-dioxane, MTBE, TBA

For more information and detailed case studies, please visit our website.

Disclaimer This information and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Recipients of this information and recommendations must make their own determination as to its suitability for their purposes. In no event shall Evonik assume liability for damages or losses of any kind or nature that result from the use of or reliance upon this information and recommendations. EVONIK EXPRESSLY DISCLAIMS ANY REPRESENTATIONS AND WARRANTIES OF ANY KIND, WHETHER EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS, NON-INFRINGEMENT, MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE (EVEN IF EVONIK IS AWARE OF SUCH PURPOSE) WITH RESPECT TO ANY INFORMATION AND RECOMMENDATIONS PROVIDED. Reference to any trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product, and does not imply that similar products could not be used. Evonik reserves the right to make any changes to the information and/or recommendations at any time, without prior or subsequent notice.

EVONIK INDUSTRIES AG
Active Oxygens
remediation@evonik.com
www.evonik.com/remediation