Product Sheet

METAFIX® REAGENTS



CUSTOMIZED METALS TREATMENT SOLUTIONS

METAFIX® represent a unique treatment approach for soil, sediment, industrial wastes, and groundwater contaminated with heavy metals.

METAFIX® Reagents are customized to cost effectively address even the most challenging site conditions.

METAFIX® Reagents are formulated blends of reducing agents, reactive minerals, mineral activators, catalysts, and pH modifiers. Following placement of METAFIX® Reagents into the treatment zone, a number of physical and chemical processes combine to create geochemical conditions under which common heavy metals are subjected to reduction, adsorption, precipitation, and conversion to stable sulfide and iron-sulfide precipitates. These heavy metal sulfide precipitates have greater stability than metal hydroxide precipitates which are formed with traditional metals treatment approaches based on pH adjustment.

Moreover, since METAFIX® utilizes multiple mechanisms, it allows for robust performance in challenging environments, with high metals concentrations, high concentrations of organic contaminants such as solvents, high salt content, or extreme pH levels.

A custom METAFIX $^{\circ}$ blend is developed based on a site's specific conditions through a low-cost treatability study to address soil and/or groundwater impacts.

KEY BENEFITS

The METAFIX® approach offers a truly one of a kind, proprietary, customized solution for the most challenging metals sites.



- The proven ability to address multiple heavy metals including; Al, As, Cd, Cu, Cr, Hg, Ni, Pb, Se, V, and Zn
- Superior Cr(VI) treatment with the formation of more stable mixed (Cr, Fe) hydroxides
- The capability of treating comingled plumes of heavy metals and chlorinated solvents
- Low overall treatment costs based on lower reagent dosing rates, as low as 0.1% – 4% (wt/wt), versus other metals treatment technologies
- The treatment mechanism is not dependent on alkalinity for removal of metals, therefore not susceptible to rebound when the matrix pH returns to ambient levels

APPLICATION METHODS

- Direct push injection
- · Hydraulic and pneumatic fracturing
- Direct soil mixing
- Permeable Reactive Barriers

For more information and detailed case studies, please visit our website.

Disclaimer This information and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Recipients of this information and recommendations must make their own determination as to its suitability for their purposes. In no event shall Evonik assume liability for damages or losses of any kind or nature that result from the use of or reliance upon this information and recommendations. EVONIK EXPRESSLY DISCLAIMS ANY REPRESENTATIONS AND WARRANTIES OF ANY KIND, WHETHER EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS, NON-INFRINGEMENT, MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE (EVEN IF EVONIK IS AWARE OF SUCH PURPOSE) WITH RESPECT TO ANY INFORMATION AND RECOMMENDATIONS PROVIDED. Reference to any trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product, and does not imply that similar products could not be used. Evonik reserves the right to make any changes to the information and/or recommendations at any time, without prior or subsequent notice.

Evonik Operations GmbH Smart Materials Active Oxygens Business Line Soil & Groundwater Remediation

remediation@evonik.com www.evonik.com/remediation

